

# TECHNICAL DATA

| Model                             |         | 118P    | 600P   |
|-----------------------------------|---------|---------|--------|
| Operating pressure                | bar     | 130     | 200    |
| Reaction force, max.              | N       | 13      | 40     |
| Turbo pressure                    | ETP-bar | 175     | 240    |
| Water quantity                    | l/h     | 780     | 1170   |
| Motor power                       | kW/HP   | 4.0/5.5 | 9.5/13 |
| Supply temperature, max.          | °C      | 70      | 80     |
| Supply pressure, max.             | bar     | 10      | 15     |
| Self-priming max. height          | m       | 5       | 5      |
| High pressure detergent           | %       |         | 0 - 5  |
| Water supply                      | *       | 3/4     | 3/4    |
| High pressure hose                | m       | 8       | 10     |
| Pump oil HYPOID 80W/90            | l       | 0,6     | 0,6    |
| Double lance high pressure nozzle | dim.    | 1505    | 1506   |
| Double lance low pressure nozzle  | dim.    | 4040    | 4040   |
| Nozzle angle                      | °       | 15/40   | 15/40  |
| Pistons                           | pce.    | 3       | 3      |
| By-pass pressure                  | bar     | 10      | 17     |
| Opening pressure                  | bar     | 155     | 225    |
| Noise level dB(A) γ*              | Lpa/Lwa | 95/108  | 99/113 |
| Length                            | mm      | 950     | 750    |
| Height                            | mm      | 680     | 700    |
| Width                             | mm      | 480     | 630    |
| Weight, complete                  | kg      | 48      | 96     |
| γ* (EN 60704-1) (EN ISO3746)      |         |         |        |